

Klübersynth GE 14-151 (H)

Version	Revision Date:	Date of last issue: 16.11.2023	Print Date:
1.10	24.05.2024	Date of first issue: 08.04.2016	24.05.2024

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Klübersynth GE 14-151 (H)

Article-No. : 012364

Manufacturer or supplier's details

Company name of supplier : Klüber Lubrication München GmbH & Co. KG
Geisenhausenerstr. 7
81379 München
Deutschland
Tel.: +49 (0) 89 7876 0
Fax: +49 (0) 89 7876 333
info@klueber.com

E-mail address of person responsible for the SDS : mcm@klueber.com

National contact : Klüber Lubrication India Private Limited
347-A, Hebbal Industrial Area,
P.O. Metagalli
Mysore 570 016
India
Tel.: +91 821 6647 041
Fax: +91 821 2402 825
customercare@in.klueber.com

Emergency telephone number : +91 821 6647 041 (9:30 am - 6:00 pm, daily except sunday)
+49 89 7876 700 (24 hrs)

Recommended use of the chemical and restrictions on use

Recommended use : Grease

Restrictions on use : Restricted to professional users.

2. HAZARDS IDENTIFICATION

Manufacture, Storage and Import of Hazardous Chemicals Rules 1989

Classification

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Klübersynth GE 14-151 (H)

Version	Revision Date:	Date of last issue: 16.11.2023	Print Date:
1.10	24.05.2024	Date of first issue: 08.04.2016	24.05.2024

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Synthetic hydrocarbon oil
ester oil
aluminium complex soap
solid lubricant

Components

Chemical name	CAS-No.	Concentration (% w/w)
disodium sebacate	17265-14-4	$\geq 2.5 - < 10$
White mineral oil (petroleum)	8042-47-5	$\geq 1 - < 10$
Molybdenum, bis(dibutylcarbamodithioato)di- μ -oxodioxodi-, sulfurized	68412-26-0	$\geq 1 - < 2.5$

4. FIRST AID MEASURES

If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If breathing is irregular or stopped, administer artificial respiration.

In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
Wash off with soap and water.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
If eye irritation persists, consult a specialist.

If swallowed : Move the victim to fresh air.
Do not induce vomiting without medical advice.

Most important symptoms and effects, both acute and delayed : None known.
No symptoms known or expected.

Notes to physician : Treat symptomatically.

Klübersynth GE 14-151 (H)

Version	Revision Date:	Date of last issue: 16.11.2023	Print Date:
1.10	24.05.2024	Date of first issue: 08.04.2016	24.05.2024

5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Unsuitable extinguishing media : High volume water jet
- Hazardous combustion products : Carbon oxides
Nitrogen oxides (NO_x)
Sulphur oxides
Oxides of phosphorus
Metal oxides
- Specific extinguishing methods : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
Exposure to decomposition products may be a hazard to health.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Do not breathe vapours, aerosols.
Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Try to prevent the material from entering drains or water courses.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Pick up and transfer to properly labelled containers.

7. HANDLING AND STORAGE

- Advice on safe handling : For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after handling the product.
- Conditions for safe storage : Store in original container.
Keep container closed when not in use.
Keep in a dry, cool and well-ventilated place.
Containers which are opened must be carefully resealed and

Klübersynth GE 14-151 (H)

Version	Revision Date:	Date of last issue: 16.11.2023	Print Date:
1.10	24.05.2024	Date of first issue: 08.04.2016	24.05.2024

kept upright to prevent leakage.
Store in accordance with the particular national regulations.
Keep in properly labelled containers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
(benzoato-O,O')hydroxy(octadecanoato-O,O')aluminium	54326-11-3	TWA (Inhalable particulate matter)	10 mg/m ³	ACGIH (2018-03-20)
		TWA (Respirable particulate matter)	3 mg/m ³	ACGIH (2018-03-20)
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m ³	IN OEL (2007-06-04)
		STEL (Mist)	10 mg/m ³	IN OEL (2007-06-04)
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH (2013-03-01)

Engineering measures : none

Personal protective equipment

Respiratory protection : Not required; except in case of aerosol formation.

Filter type : Filter type P

Hand protection

Material : Nitrile rubber

Break through time : > 10 min

Protective index : Class 1

Remarks : For prolonged or repeated contact use protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

Eye protection : Safety glasses

Skin and body protection : Choose body protection in relation to its type, to the

Klübersynth GE 14-151 (H)

Version 1.10	Revision Date: 24.05.2024	Date of last issue: 16.11.2023 Date of first issue: 08.04.2016	Print Date: 24.05.2024
-----------------	------------------------------	---	---------------------------

concentration and amount of dangerous substances, and to the specific work-place.

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : yellow

Odour : characteristic

Odour Threshold : No data available

pH : Not applicable

Melting point/range : No data available

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : Combustible Solids

Self-ignition : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : < 0.001 hPa (20 °C)

Relative vapour density : No data available

Klübersynth GE 14-151 (H)

Version 1.10	Revision Date: 24.05.2024	Date of last issue: 16.11.2023 Date of first issue: 08.04.2016	Print Date: 24.05.2024
-----------------	------------------------------	---	---------------------------

Relative density	:	0.93 (20 °C) Reference substance: Water The value is calculated
Density	:	0.93 g/cm ³ (20 °C)
Bulk density	:	No data available
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	No data available
Sublimation point	:	No data available
Particle size	:	Not applicable

10. STABILITY AND REACTIVITY

Reactivity	:	No hazards to be specially mentioned.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	No dangerous reaction known under conditions of normal use.
Conditions to avoid	:	No conditions to be specially mentioned.
Incompatible materials	:	No materials to be especially mentioned.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

Klübersynth GE 14-151 (H)

Version	Revision Date:	Date of last issue: 16.11.2023	Print Date:
1.10	24.05.2024	Date of first issue: 08.04.2016	24.05.2024

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Remarks: This information is not available.

Acute inhalation toxicity : Remarks: This information is not available.

Acute dermal toxicity : Remarks: This information is not available.

Components:

disodium sebacate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
GLP: no

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes
Assessment: The substance or mixture has no acute dermal toxicity

White mineral oil (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Molybdenum, bis(dibutylcarbamodithioato)di-μ-oxodioxodi-, sulfurized:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 420
GLP: yes
Assessment: The substance or mixture has no acute oral toxicity

Klübersynth GE 14-151 (H)

Version	Revision Date:	Date of last issue: 16.11.2023	Print Date:
1.10	24.05.2024	Date of first issue: 08.04.2016	24.05.2024

Acute inhalation toxicity : LC50 (Rat): > 34.4 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 10,000 mg/kg

Skin corrosion/irritation

Product:

Remarks : This information is not available.

Components:

disodium sebacate:

Species : Rabbit
Assessment : No skin irritation

Method : OECD Test Guideline 404
Result : No skin irritation
GLP : no

White mineral oil (petroleum):

Species : Rabbit
Assessment : No skin irritation

Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

Molybdenum, bis(dibutylcarbamodithioato)di-μ-oxodioxodi-, sulfurized:

Assessment : No skin irritation

Method : OECD Test Guideline 439
Result : No skin irritation
GLP : yes

Serious eye damage/eye irritation

Product:

Remarks : This information is not available.

Components:

disodium sebacate:

Species : Rabbit
Assessment : Irritating to eyes.
Method : OECD Test Guideline 437
Result : Irritating to eyes.

Klübersynth GE 14-151 (H)

Version	Revision Date:	Date of last issue: 16.11.2023	Print Date:
1.10	24.05.2024	Date of first issue: 08.04.2016	24.05.2024

GLP : yes

White mineral oil (petroleum):

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : yes

Molybdenum, bis(dibutylcarbamodithioato)di-μ-oxodioxodi-, sulfurized:

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : yes

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

disodium sebacate:

Species : Guinea pig
Assessment : Did not cause sensitisation on laboratory animals.
Result : Did not cause sensitisation on laboratory animals.

White mineral oil (petroleum):

Test Type : Buehler Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.
GLP : yes

Molybdenum, bis(dibutylcarbamodithioato)di-μ-oxodioxodi-, sulfurized:

Species : Mouse
Assessment : Did not cause sensitisation on laboratory animals.
Method : OECD Test Guideline 429
Result : Did not cause sensitisation on laboratory animals.
GLP : yes

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Klübersynth GE 14-151 (H)

Version	Revision Date:	Date of last issue: 16.11.2023	Print Date:
1.10	24.05.2024	Date of first issue: 08.04.2016	24.05.2024

Genotoxicity in vivo : Remarks: No data available

Components:

disodium sebacate:

Germ cell mutagenicity - Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

White mineral oil (petroleum):

Germ cell mutagenicity - Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Molybdenum, bis(dibutylcarbamodithioato)di- μ -oxodioxodi-, sulfurized:

Germ cell mutagenicity - Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Carcinogenicity

Product:

Remarks : No data available

Components:

White mineral oil (petroleum):

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

Components:

disodium sebacate:

Reproductive toxicity - Assessment : - Fertility -
No toxicity to reproduction
- Teratogenicity -
No effects on or via lactation

White mineral oil (petroleum):

Klübersynth GE 14-151 (H)

Version	Revision Date:	Date of last issue: 16.11.2023	Print Date:
1.10	24.05.2024	Date of first issue: 08.04.2016	24.05.2024

Reproductive toxicity - Assessment : - Fertility -
No toxicity to reproduction
- Teratogenicity -
No effects on or via lactation

Molybdenum, bis(dibutylcarbamodithioato)di-μ-oxodioxodi-, sulfurized:

Reproductive toxicity - Assessment : - Fertility -
No toxicity to reproduction

STOT - single exposure

Product:

Remarks : No data available

Components:

White mineral oil (petroleum):

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure

Product:

Remarks : No data available

Components:

White mineral oil (petroleum):

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

Product:

This information is not available.

Components:

disodium sebacate:

No aspiration toxicity classification

Klübersynth GE 14-151 (H)

Version	Revision Date:	Date of last issue: 16.11.2023	Print Date:
1.10	24.05.2024	Date of first issue: 08.04.2016	24.05.2024

White mineral oil (petroleum):

May be fatal if swallowed and enters airways.

Molybdenum, bis(dibutylcarbamodithioato)di- μ -oxodioxodi-, sulfurized:

No aspiration toxicity classification

Further information

Product:

Remarks : Information given is based on data on the components and the toxicology of similar products.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other :
aquatic invertebrates Remarks: No data available

Toxicity to algae/aquatic :
plants Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

disodium sebacate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates Exposure time: 48 h
Test Type: semi-static test
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic : EL50 (Skeletonema costatum (marine diatom)): 38.7 mg/l
plants Exposure time: 72 h
Test Type: static test
Method: ISO 10253
GLP: yes

Klübersynth GE 14-151 (H)

Version	Revision Date:	Date of last issue: 16.11.2023	Print Date:
1.10	24.05.2024	Date of first issue: 08.04.2016	24.05.2024

White mineral oil (petroleum):

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to microorganisms : LC50 (Bacteria): > 1,000 mg/l
Exposure time: 40 h
Test Type: Growth inhibition
- Toxicity to fish (Chronic toxicity) : NOEC: > 100 mg/l
Exposure time: 28 d
Species: Oncorhynchus mykiss (rainbow trout)
Remarks: The value is given based on a SAR/AAR approach using OECD Toolbox, DEREK, VEGA QSAR models (CAESAR models), etc.
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: >= 1,000 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Remarks: The value is given based on a SAR/AAR approach using OECD Toolbox, DEREK, VEGA QSAR models (CAESAR models), etc.

Molybdenum, bis(dibutylcarbamodithioato)di-μ-oxodioxodi-, sulfurized:

- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: semi-static test
- Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l
Exposure time: 72 h
Test Type: static test

Ecotoxicology Assessment

- Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

Persistence and degradability

Product:

Klübersynth GE 14-151 (H)

Version	Revision Date:	Date of last issue: 16.11.2023	Print Date:
1.10	24.05.2024	Date of first issue: 08.04.2016	24.05.2024

Biodegradability : Remarks: No data available

Physico-chemical
removability : Remarks: No data available

Components:

disodium sebacate:

Biodegradability : Result: Biodegradable
Biodegradation: 89 %
Exposure time: 28 d

White mineral oil (petroleum):

Biodegradability : Biodegradation: 31 %
Exposure time: 28 d

Molybdenum, bis(dibutylcarbamodithioato)di-μ-oxodioxodi-, sulfurized:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301
GLP: yes

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

disodium sebacate:

Partition coefficient: n- : log Pow: -4.9 (20 °C)
octanol/water pH: 7.8

White mineral oil (petroleum):

Partition coefficient: n- : log Pow: > 6
octanol/water

Molybdenum, bis(dibutylcarbamodithioato)di-μ-oxodioxodi-, sulfurized:

Partition coefficient: n- : log Pow: 6.24 - 7.28
octanol/water

Mobility in soil

Product:

Mobility : Remarks: No data available

Klübersynth GE 14-151 (H)

Version 1.10	Revision Date: 24.05.2024	Date of last issue: 16.11.2023 Date of first issue: 08.04.2016	Print Date: 24.05.2024
-----------------	------------------------------	---	---------------------------

Distribution among environmental compartments : Remarks: No data available

Other adverse effects

Product:

Additional ecological information : No information on ecology is available.

Components:

White mineral oil (petroleum):

Results of PBT and vPvB assessment : Substance is not persistent, bioaccumulative, and toxic (PBT).

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Dispose of waste product or used containers according to local regulations.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Special precautions for user

Not applicable

Klübersynth GE 14-151 (H)

Version	Revision Date:	Date of last issue: 16.11.2023	Print Date:
1.10	24.05.2024	Date of first issue: 08.04.2016	24.05.2024

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Montreal Protocol	:	Not applicable
Rotterdam Convention (Prior Informed Consent)	:	Not applicable
Stockholm Convention (Persistent Organic Pollutants)	:	Not applicable

16. OTHER INFORMATION

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
IN OEL	:	India. Permissible levels of certain chemical substances in work environment.

ACGIH / TWA	:	8-hour, time-weighted average
IN OEL / TWA	:	Time-Weighted Average Concentration (TWA) (8 hrs.)
IN OEL / STEL	:	Short-term exposure Limit STEL (15 min)

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines

Klübersynth GE 14-151 (H)

Version	Revision Date:	Date of last issue: 16.11.2023	Print Date:
1.10	24.05.2024	Date of first issue: 08.04.2016	24.05.2024

Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.